Preventing Ladder Falls

What this Toolbox Talk Covers:

✓ The "Dos" and "Don'ts" of ladder safety.

Discussion Leader Duties:

✓ Demonstrate the proper way to use ladders, including positioning and fall protection measures.

Discussion Notes:

- ✓ Discuss the outcomes of the "Dos" and "Don'ts"
- **Do** Safely position ladders each time they are used.
 - Ensure ladders do not slip from their supports and are securely positioned.
 - Know how much weight your ladder is designed to support.
 - Use ladders that are compliant with OSHA standards.
 - Inspect ladders prior to use to ensure there are no damages or cracks.
 - Position ladders so the side rails extend at least three feet beyond the top surface.
 - Keep at least three points of your body in contact with the ladder at all times when climbing (e.g., two feet and one hand).
- **Don't** Reach outside the ladder side rails. Prevent loss of balance by moving the ladder so you do not have to reach.
 - Put ladders on unstable or slippery surfaces.
 - Move or adjust a ladder while a person or equipment is on it.
 - Stand on the top cap of a stepladder.
 - Set up ladders in busy or high traffic areas.

Discussion questions:

- 1. What factors should you include when considering a ladder's maximum intended load?
- 2. Why should ladders be set up in low traffic areas?
- 3. Why should you face the ladder when climbing or descending?
- 4. How often should ladders be inspected for damage or defects?

Meeting note:

Employee comments/concerns:					
Other safety issues t	to be addressed on the job	/facility:			
Training record:	Date:	Jobsite/Facility:			
	Trainer:	Title:			
Employee name		Employee name			
(print)	/ (signature)	(print)	/ (signature)		
	1	,	1		
	/		/		
	/		/		
·	/		/		
-	1		1		

(Continue recording signatures on a separate sheet of paper)

Employee Quiz is provided on last page. Answers are: 1. (b), 2. (d), 3. (c), 4. (b), 5. (c)



Preventing Ladder Falls

Hazards include:

Ladder falls can result in serious injury or even death.

Smart Safety Rules

- Always face the ladder when climbing or descending.
- When using a job-made ladder, ensure that the rungs are equally spaced and there are no sharp edges or nails jutting out that might catch on clothing or cause injury.
- Position ladders that are designed to lean against a
 wall or other support so that the horizontal distance
 from the top support to the foot of the ladder is
 approximately ¼ the working length of the ladder.
- Keep the area around the top and bottom of the ladder clear.
- Do not carry loads up and down the ladder with you, as this increases your chance for losing your balance and falling.



Employee Quiz Topic: Ladder Safety

Employee Nam			
Circle the corre	ct answer below.		
	limb a ladder while carrying as long as you have one free	4. While on a ladder, it is accepoutside the side railings to r location.a. Trueb. False	
important f ladders? a. Rungs a b. No mis c. No nail	ne following guidelines are for constructing job-made are equally spaced sing steps or rungs s or sharp edges sticking out ne above	5. When using a 20-foot leanir far above the top surface she ladder extend? a. At least 5 ft. b. At least 2 ft. c. At least 3 ft. d. At least 1 ft.	_
surface? a. Woode b. Concre	te surfaces surfaces		
aining record:	Date:	Jobsite/Facility:	
	Trainer:	Title:	